



 **First in Quality. Built to Last.**

BUNDLING TUNNELS PROFESSIONAL SERIES

MODELS

STB2416, STB2420, STB3616, STB3620, STB4816,
STB4820, STB5616, STB5620, STB7016, STB7020, STB8020

BUILT RIGHT...PRICED RIGHT

Proven reliable over and over again, Streamline Solutions bundling tunnels provide you with all the quality features found in much higher priced machines. They are designed and built to give you all the features needed for positive shrinking of polyethylene film.

RUGGED DESIGN

Streamline Solutions top of the line bundling tunnels are expertly welded on 12 gauge steel frames and designed to handle the day to day abuse of most bundling applications. Each tunnel utilizes four-directional variable air flow to provide a positive shrink. See for yourself why Streamline Solutions has been a leader in the shrink packaging industry for over 25 years.

STANDARD FEATURES

- Designed to shrink polyethylene film.
- All-welded main frame from 12 gauge steel
- 78" chamber length to ensure proper shrinking of film
- High temperature belting resists wear



RELIABLE SHRINK PERFORMANCE

Streamline Solutions' STB Series bundling tunnels offer the reliability needed to provide positive shrinking and are designed specifically for bundling applications.

STANDARD FEATURES (cont.)

- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable digital solid state temperature control for a variety of films
- Four-directional air flow provides positive shrinking
- Variable air flow for a variety of products and applications
- Large ducting creates more air volume inside tunnel
- Airflow extended to the end of the chamber sides
- 4' product cooling conveyor on exit end
- Exit cooling fans accelerate shrinking
- Delayed cool down and over temperature protection
- Fold down electrical control panel for easy maintenance
- Heavy duty casters for transportation within plant
- Leveling legs provide sturdy base once in place
- Custom two part epoxy finish resists scratching
- Available in 220v - single or 3-phase
- Easy to use design requires minimal training, maintenance, and trouble free operation
- Made in the USA

OPTIONS

- Wipe down rollers - standard or pneumatic
- Raised hood - additional 4" or 8" product height
- UL approved electronics and control box
- Left hand machines available
- Custom sizes and configurations available upon request

**Ask Us About Custom Equipment*

www.streamlinesolutionsusa.com

BUNDLING TUNNELS PROFESSIONAL SERIES



1. Reliable Shrink Performance

Proven Streamline Solutions tunnels provide positive shrinking of polyolefin, polyethylene and PVC films

2. High Temperature Belting

High temperature belting resists wear and is designed specifically for polyethylene films

3. Control Panel

Easy to use control panel lets users adjust for their specific application

4. Variable Air Flow

Four directional air flow provides positive shrinking for a variety of products and applications

MODEL NUMBER	MACHINE DIMENSIONS			CHAMBER DIMENSIONS			CONVEYOR LENGTH	STANDARD POWER			WEIGHT SHP WT.	
	WIDTH (A)	HEIGHT (B)	LENGTH (C)	WIDTH	HEIGHT	LENGTH		VOLTS	AMPS	PHASE		
STB2416	43"	56"- 72"	149"	24"	16" - 20"	78"	147"	480	30	3	1900 lbs	2000 lbs
	109 cm	142-182 cm	378 cm	60 cm	40 - 50 cm	198 cm	373 cm				861 kg	908 kg
STB2420	43"	56"- 72"	149"	24"	16" - 20"	78"	147"	480	50	3	1900 lbs	2000 lbs
	109 cm	142-182 cm	378 cm	60 cm	40 - 50 cm	198 cm	373 cm				861 kg	908 kg
STB3616	55"	56"- 72"	149"	36"	16" - 20"	78"	147"	480	60	3	2200 lbs	2300 lbs
	139 cm	142-182 cm	378 cm	91 cm	40 - 50 cm	198 cm	373 cm				997 kg	1043 kg
STB3620	55"	56"- 72"	149"	36"	16" - 20"	78"	147"	480	50	3	2200 lbs	2300 lbs
	139 cm	142-182 cm	378 cm	91 cm	40 - 50 cm	198 cm	373 cm				997 kg	1043 kg
STB4816	67"	56"- 72"	149"	48"	16" - 20"	78"	147"	480	100-120	3	2600 lbs	2700 lbs
	170 cm	142-182 cm	378 cm	121 cm	40 - 50 cm	198 cm	373 cm				1179 kg	1224 kg
STB4820	67"	56"- 72"	149"	48"	16" - 20"	78"	147"	480	100-120	3	2600 lbs	2700 lbs
	170 cm	142-182 cm	378 cm	121 cm	40 - 50 cm	198 cm	373 cm				1179 kg	1224 kg
STB5616	75"	56"- 72"	149"	56"	16" - 20"	78"	147"	480	100-120	3	2900 lbs	3000 lbs
	190 cm	142-182 cm	378 cm	142 cm	40 - 50 cm	198 cm	373 cm				1315 kg	1360 kg
STB5620	75"	56"- 72"	149"	56"	16" - 20"	78"	147"	480	100-120	3	2900 lbs	3000 lbs
	190 cm	142-182 cm	378 cm	142 cm	40 - 50 cm	198 cm	373 cm				1315 kg	1360 kg
STB7016	89"	56"- 72"	149"	70"	16" - 20"	78"	147"	480	100-120	3	3200 lbs	3300 lbs
	226 cm	142-182 cm	378 cm	177 cm	40 - 50 cm	198 cm	373 cm				1451 kg	1496 kg
STB7020	89"	56"- 72"	149"	70"	16" - 20"	78"	147"	480	100-120	3	3200 lbs	3300 lbs
	226 cm	142-182 cm	378 cm	177 cm	40 - 50 cm	198 cm	373 cm				1451 kg	1496 kg
STB8020	99"	56"- 72"	149"	80"	20"	78"	147"	480	100-120	3	3500 lbs	3600 lbs
	251 cm	142-182 cm	378 cm	203 cm	50 cm	198 cm	373 cm				1587 kg	1632 kg



STREAMLINE SOLUTIONS™

(866)244-7700

www.streamlinesolutionsusa.com
info@streamlinesolutionsusa.com
P.O. Box 560775, Orlando, FL 32856