

Streamline Solutions

Shrink Sleeve Labeling & Tamper Evident Banding

ECONOMICAL SHRINK LABELING

The SX-150 Shrink Sleeve Label and Tamper Evident Band applicator from Streamline Solutions is a mid-range labeling machine designed for middle, full body, and full body and cap applications. The SX-150 is designed for low to moderate production rates and is a perfect solution for industries including food and beverage, pharmaceutical, nutraceutical, health and beauty, consumer goods, chemical, and other manufactured goods. Due to the versatility of the system, the SX-150 is also ideal for the changing needs of contract packagers.

INCREASE YOUR WORKFLOW

SX-150 is an in-line single-head mandrel style labeling system engineered to meet the demand of your workflow. The SX-150 can be rolled up to any conveyor to provide accurate shrink sleeve placement up to 300 products per minute. The machine's sturdy design and construction provides for 24 hour operation, while its' standard dual unwind system allows continued operation with only a brief splicing stop. Product runs are programmed with the user-friendly touch-screen control panel HMI, featuring standard and custom menus that can be password protected for an added layer of security.

VERSATILITY AND RELIABILITY

Every SX Series machine is designed with servo driven, PLC controlled label drive rollers, cutter assembly, and label shooting wheels to provide accurate and consistent shrink sleeve labeling. SX-150 is constructed using 304 grade

stainless steel to provide strength and reduce vibration while offering quiet operation. SX-150 has been engineered to handle oval and round containers made of plastic, glass, or metal at speeds of up to 300cpm. Users also have the option of purchasing additional mandrels for non-cylindrical containers. The multiple blade rotational cutting mechanism provides extremely smooth, even cutting of film ranging from 35 microns up to 70 microns.

GUARANTEED PRECISION. QUICK CHANGEOVER.

Size change overs are simple and quick. The cut length can be changed electronically by utilizing the control panels' touch screen interface. For different product diameters, a new timing screw and bullet (mandrel) can be installed in minutes, while different product heights are accommodated by raising or lowering the machine with a turn-screw mechanism. The SX-150 comes with our quick change system for switching mandrels with a turn of a knob. Along with the mandrel, the cutter assembly has only two levers to turn, keeping your downtime to a minimum.

THE RIGHT CHOICE

Rugged design. Maximum uptime. Lower cost of ownership. Your benefits go on and on. When it comes to shrink sleeve and tamper band application, rely on Streamline Solutions to provide the right solution for your shrink sleeve labeling needs.





| TECHNICAL SPECIFICATIONS | |
|--------------------------|---|
| Power | 220V/3ph/20A or 480V/3ph/10A; 50/60 Hz |
| Film Thickness | 0.035mm - 0.07mm |
| Film Lay Flat | 40mm - 240mm* |
| Cut Length | 40mm - 200mm, or modification to 70mm - 250mm |
| Machine Dimensions | 853mm (W) x 1090mm (L) x 1850-2150mm (H)* 33.6" (W) x 42.9" (L) x 72.8" - 84.6" (H)* |
| Speed | 50 - 300CPM |

 $^{^{\}star}$ SX models available to accommodate wider film lay flat. Please inquire about the SX models from your Authorized Distributor or Streamline Solutions Representative.

Make your products stand out among the competition with Streamline Solutions Shrink Sleeves and Tamper Evident Banding









©2022 streamline Solutions. Specifications subject to change. All trademarks are the property of their respective owners. Product samples shown illustrate the capabilities of Streamline Solutions and do not necessarily represent a business relationship between the companies.











1. Smooth and Even Film Cutting

The multiple-blade rotational cutting mechanism provides smooth and even cutting at high speeds

2. Dual Roll Unwind System

Standard dual roll film unwind and tension control systems maintain optimal in-feed tension needed for high speed operations

3. In-line Single-Head Mandrel

The bullet style mandrel is ideal for oval and round containers made of plastic, glass, or metal

4. Simple Conveyor Height Adjustment

Easy-to-use hand crank allows for ideal height adjustment on virtually any conveyor.

STANDARD COMPONENTS:

- Round cylindrical mandrel
- Round Cutter
- Single round 400 mm timing screw
- Photo eye for registered cutting
- Label brush down device
- Dual roll unwind system and tension control
- Thermal transfer overprinter

OPTIONAL FEATURES & COMPONENTS

- Irregular mandrel, timing screw, and cutter for non-cylindrical containers
- Dual belt drive system for stopping label for mid-body label applications
- Vertical and T-Perforation units
- Label tamp down device
- Dual 400mm and 800mm timing screw assemblies for irregualr containers
- XL models available

(866)244-7700 www.streamlinesolutionsusa.com P.O. Box 560775, Orlando, FL 32856